




Bou



BOU | CL - 010401 | Downlight



CARACTERISTICAS

AMPERAJE	350mA
POTENCIA	1X5 W
CRI	>80

COLOR - LM

3000° K	280 lm
4000° K	300 lm
5000° K	320 lm


OPTICA

20°

25°

60°

BOU | CL - 010402 | Downlight



CARACTERISTICAS

AMPERAJE	500mA
POTENCIA	1X10 W
CRI	>80

COLOR - LM

3000° K	580 lm
4000° K	600 lm
5000° K	620 lm


OPTICA

20°

40°

60°

BOU | CL - 010403 | Downlight



CARACTERISTICAS

AMPERAJE	1100mA
POTENCIA	1X15 W
CRI	>80

COLOR - LM

3000° K	880 lm
4000° K	900 lm
5000° K	920 lm

OPTICA

20°


40°

60°





CL-0104-A01
Ø 95mm



CL-0104-A02
Ø 95mm



CL-0104-A03
Ø 70mm



CL-0104-A04
Ø 95mm



CL-0104-A05
95X95mm



CL-0104-A06
Ø 95mm



CL-0104-A07
Ø 95mm



CL-0104-A08
300x100mm



CL-0104-A09
190x95mm



CL-0104-A10
95x95mm



CL-0104-A11
190x95mm



